



**PRESTAZIONI
Performance
Leistungen**

Rt 1:1

RPM max 6.000

Max carico assiale
Max axial load
Längsbelastung max. 1250 N

Momento torcente
Torque
Drehmoment 45 Nm

Adduzione refrig. interna
Internal coolant
Ik No

Mandrino
Spindle
Spindel ER-32

Senso di rotazione
Direction of rotation
Drehrichtung 

Descrizione/Description/Beschreibung

M90-3.5 ER-32

Codice Alberti/Alberti Code/Albertinummer

ANK.W15.0200.32

DOTAZIONE STANDARD / STANDARD EQUIPMENT

Libro istruzioni
Instruction book
Gebrauchsanweisung

Chiavi di servizio
Service key
Bedien Schlüssel

NAKAMURA

Costruttore/Builder/Hersteller

9.92.3.55.08

Alberti Umberto



Teste angolari e motorizzazioni
Via CORZIA, 37 - 21047 SAKONNOVA
e-mail: info@albertiumberto.it
http://www.albertiumberto.it

Tel. (02) 96703586 (2 linee r.a.) FAX (02) 96703620

Modello/Model

**SUPER NTJ-NTJX / NTM3 / TMC18 / TW10
SC150-250 / WT150-250 / WTW150 / WTS150**

MOTORIZZATO RADIALE

Radial driven tool

Radial werkzeug