



**PRESTAZIONI  
Performance  
Leistungen**

Rt	1:1
RPM max	6.000
Max carico assiale Max axial load Längsbelastung max.	800 N
Momento torcente Torque Drehmoment	20 Nm
Adduzione refrig. interna Internal coolant Ik	No
Mandrino Spindle Spindel	ER-25
Senso di rotazione Direction of rotation Drehrichtung	

**DOTAZIONE STANDARD / STANDARD EQUIPMENT**

Libro istruzioni  
Instruction book  
Gebrauchsanweisung

9.97.2.55.00

Chiavi di servizio  
Service key  
Bedienschlüssel

**NAKAMURA**

Costruttore/Builder/Hersteller

**Alberti Umberto**

Teste angolari e motorizzazioni  
Via CORZIA, 37 - 21047 SARONNOVA  
e-mail: info@albertiumberto.it  
http://www.albertiumberto.it

Tel. (02) 96703586 (2 linee r.a.) FAX (02) 96703620

Modello/Model

**SUPER NTJ-NTJX / NTM3 / TMC18 / TW10  
SC150-250 / WT150-250 / WTW150 / WTS150**

**RADIALE ARRETRATO / OFFSET RADIAL TOOL**

**Radialzurückgesetztes Werkzeug**

**M90-2,5 D ER-25**

Descrizione/Description/Beschreibung

**KZ1513D-ER25**

Codice Alberti/Alberti Code/Albertinummer

**ANK.W15.0700**