



**PRESTAZIONI  
Performance  
Leistungen**

Rt	2:1
RPM max	12.000
Max carico assiale Max axial load Längsbelastung max.	480 N
Momento torcente Torque Drehmoment	18 Nm
Adduzione refrig. interna Internal coolant Ik	No
Attacco rapido Quick-change Schnittstelle	ER-16A
Senso di rotazione Direction of rotation Drehrichtung	

**DOTAZIONE STANDARD / STANDARD EQUIPMENT**

Libro istruzioni  
Instruction book  
Gebrauchsanweisung

Chiavi di servizio  
Service key  
Bedienschlüssel

**MOTORIZZATO RADIALE**

Radial driven tool  
Radial werkzeug

9.92.2.44.S0

Costruttore/Builder/Hersteller

**NAKAMURA**

Modello/Model

WT-100 / NTY-3

Descrizione/Description/Beschreibung

**M90-2.5 ER-16A**

Codice Alberti/Alberti Code/Albertinummer

**ANK.W10.020S**



**Alberti Umberto**

Teste angolari e motorizzazioni  
Via CORZIA, 37 - 21047 SARONNOVA

e-mail: [info@albertiumberto.it](mailto:info@albertiumberto.it)  
<http://www.albertiumberto.it>

Tel. (02) 96703586 (2 linee r.a.) FAX (02) 96703620