

**PRESTAZIONI  
Performance  
Leistungen**

Rt 1:1

RPM max 6.000

Max carico assiale  
Max axial load 800 N  
Längsbelastung max.

Momento torcente  
Torque 20 Nm  
Drehmoment

Adduzione refrig. interna  
Internal coolant Yes  
Ik

Mandrino  
Spindle ER-25  
Spindel

Senso di rotazione  
Direction of rotation  
Drehrichtung



**DOTAZIONE STANDARD / STANDARD EQUIPMENT**

Libro istruzioni  
Instruction book  
Gebrauchsanweisung

Chiavi di servizio  
Service key  
Bedienschlüssel

**NAKAMURA**

**RADIALE / RADIAL TOOL**

**RADIALWERKZEUG**

**KZ1513C-ER25**

Descrizione/Description/Beschreibung

Costruttore/Builder/Hersteller

**NAKAMURA**

**RADIALE / RADIAL TOOL**

**RADIALWERKZEUG**

**KZ1513C-ER25**

Descrizione/Description/Beschreibung

**9.92.2.55.C3**


Modello/Model

**SUPER NTJ-NTJX / NTM3 / TMC18 / TW10  
SC150-250 / WT150-250 / WTW150 / WTS150**

**M90-2,5 ER-25 R.I.70BAR**

Codice Alberti/Alberti Code/Albertinummer

**ANK.W15.020C**



**Alberti Umberto**

Teste angolari e motorizzazioni  
Via CORZIA, 37 - 21047 SARONNO(VA)

e-mail: [into@albertumberto.it](mailto:into@albertumberto.it)  
<http://www.albertumberto.it>

Tel. (02) 96703586 (2 linee r.a.) FAX (02) 96703620